SUPPLIER COMPLIANCE STATEMENT FOR APPLICATIONS IN FOOD CONTACT

EMS-CHEMIE AG, Business Unit EMS-GRIVORY Europe, hereby declares that its product

Grilamid L 25 natural

chemically consisting of PA 12 (designation according to ISO 1043), is regulated in contact with foodstuff in the European Union, in Germany and in the USA as follows:

European Union

Grilamid L 25 natural meets the relevant requirements laid down in Regulation (EC) No. 1935/2004 as amended and is in compliance with Regulation (EC) No. 10/2011 of 14. January 2011, which is consolidating the EU-Directives 2002/72 of 6. August 2002, 2004/01 of 6. January 2004, 2004/19 of 1. March 2004, 2005/79 of 18. November 2005, 2007/19 of 2. April 2007, 2008/39 of 6. March 2008 and Regulation (EC) No. 975/2009 of 19. October 2009.

Requirements:

Global migration limit (OML):

Specific migration limit (SML):

Laurolactam (Ref. No. 19490, CAS No. 947-04-6):

5.0 mg/kg

Germany

Grilamid L 25 natural is in compliance with the Consumer Goods Ordinance (Bedarfsgegenständeverordnung) of December 23, 1997, published in Bundesgesetzblatt 1998, part I, page 5, as currently amended, which corresponds to the Directive 2002/72/EC as amended.

The requirements are the same as in the European Union.

USA

Grilamid L 25 natural is in compliance with FDA regulations 21 CFR 177.1500 (9) for the nylon grade. This product does not contain additives.

Restrictions: For direct food contact the thickness must not exceed 41 µm. For indirect or repeated food contact also higher thickness is possible. Use only with non-alcoholic food and beverages.

General requirements for all countries

Producers of the final articles coming into contact with food have to perform migration tests to control that the migration limits and other requirements are fulfilled. Furthermore it must be assured that the composition and organoleptic characteristics of the food are not changed to an unacceptable extent.

Domat/Ems, 04 February 2011

I. Bersdy

Dr. Thomas Emerschitz Regulatory Affairs

Dr. Jürgen Müller Quality Assurance / Material Testing

Tel.

Fax

+41 81 632 7184

+41 81 632 7434